

LOC/DME I-BYW 110.9 Chan 46	APP CRS 091°	Rwy Ldg TDZE 7500 680 Apt Elev 680	ILS PRM Y RWY 10R (CLOSE PARALLEL) CHICAGO O'HARE INTL (ORD)
---	------------------------	--	---

RNAV 1-GPS or RADAR required for procedure entry. DME or RADAR required.
From GIBNS: RNAV-1 GPS required.

Simultaneous approach authorized. Use of FD or AP required during simultaneous operations. Dual VHF Comm required.
See additional requirements on AAUP.

ALSIF-2

MISSED APPROACH: Climb to 1200 then climbing right turn to 4000 direct DPA VOR/DME and hold.

D-ATIS 135.4 282.225	CHICAGO APP CON 119.0 292.125	O'HARE TOWER 133.0 348.0 PRM 128.05	124.125 GND CON (TWR CENTER) 118.05 (TWR NORTH) 226.675 (TWR SOUTH) 121.9 (TWR SOUTH) (OBND) 121.9 (TWR SOUTH) (IBND)	CLNC DEL 121.6	CPDLC
--	---	---	--	--------------------------	-------

MSA ORD 25 NM

3400

FERLL I-BYW [27.8] RADAR

OLLGA I-BYW [21.5] RADAR

GOOZY (IF) I-BYW [15.3] RADAR

LEATH I-BYW [18.4] RADAR

KVENN I-BYW [12.1] RADAR

FLYN INT I-BYW [6.6] RADAR

8000 7000 6000 5000 4000 2300

271° 091° (3.1) (3.1) (3.1) (3.1) (5.6)

9000 087° (20.1)

DUPAGE 114.55 DPA Chan 92(Y)

LOCALIZER 110.9 I-BYW Chan 46 LOC offset 2.50°

ALTERNATE MISSED APCH FIX JOLIET 112.3 Chan 70

1200 4000 DPA

113.0 Obk Chan 77

1468 883 813 807 1508 1185

R-248 068° 248°

R-246 066° 246°

ELEV 680 TDZE 680

FERLL I-BYW [27.8] RADAR

OLLGA I-BYW [21.5] RADAR

GOOZY I-BYW [15.3] RADAR

LEATH I-BYW [18.4] RADAR

KVENN I-BYW [12.1] RADAR

FLYN INT I-BYW [6.6] RADAR

9000 8000 7000 6000 5000 4000 2300

GS 3.00° TCH 55

3.1 NM 3.1 NM 3.1 NM 3.1 NM 3.1 NM 5.6 NM 4.9 NM

CATEGORY A B C D

S-ILS 10R 930/24 250 (300-1/2)

TWR 7500 X 150 11245 X 200 11260 X 150 13000 X 150 10800 X 200 7500 X 150

0.3% DOWN 0.3% DOWN 0.3% DOWN 0.3% UP

091°

HIRL all Rwys TDZ/CL all Rwys except 4L

CHICAGO, ILLINOIS

41°59'N-87°54'W

CHICAGO O'HARE INTL (ORD)

Orig-D 22APR21

ILS PRM Y RWY 10R (CLOSE PARALLEL)