

WAAS CH <b>86515</b> <b>W05B</b>	APP CRS <b>054°</b>	Rwy Idg <b>9000</b> TDZE <b>916</b> Apt Elev <b>926</b>
--	------------------------	---

RNAV (GPS) RWY 5L  
PIEDMONT TRIAD INTL (GSO)

RNP APCH - GPS.




**⚠** For inop ALS, increase LNAV Cat D visibility to RVR 6000. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 47°C. Simultaneous approach authorized with ILS or LOC Rwy 5R, ILS Rwy 5R (CAT II). Use of FD or AP required during simultaneous operations. LNAV procedure NA during simultaneous operations.

ALSF-2



**MISSED APPROACH:**  
Climb to 2800 direct  
TUPUE and hold.

D-ATIS <b>128.55</b>	GREENSBORO APP CON <b>124.35 269.225</b> (250°-049°) <b>126.6 327.075</b> (050°-249°)	GREENSBORO TOWER <b>119.1 290.325</b>	GND CON <b>121.9 348.6</b>	CLNC DEL <b>121.75</b>
-------------------------	---	--	-------------------------------	---------------------------



CATEGORY		A	B	C	D
LPV	DA	1116/18 200 (200-½)			
LNAV/ VNAV	DA	1367/50 451 (500-1)			
LNAV MDA		1300/24 384 (400-½)	1300/35 384 (400-¾)	1300/50 384 (400-1)	
<b>C</b> CIRCLING		1440-1 514 (600-1)	1700-2¼ 774 (800-2¼)	1700-2½ 774 (800-2½)	

TDZ/CL Rwy's 5L, 23R and 23L

REIL Rwy 32

HIRL Rwys 14-32, 5R-23L and