KEY WEST, FLORIDA

RNAV (GPS) RWY 4

APCH CRS	Rwy Idg	7001
037°	TDZE	4
	Arpt Elev	6

- (USN) KEY WEST NAS (BOCA CHICA FLD) (KNQX)

RNP APCH

RADAR required

T

MISSED APPROACH: (Do not exceed 230 KIAS until CEGEX.) Climb to 1600 direct CEGEX, track 314° to FISLI, track 229° to SKIPP and hold.

ATIS★	APP CON	NAVY KEY WEST TOWER★	GND CON	CLNC DEL	ASR/PAR
307.025	124.025 313.7	118.575 340.25	121.7 336.45	121.2 357.4	

CONTIGUOUS US ADIZ

FISLI

CAUTION: Balloon with strobe light on unmarked cable to 14,000 in R-2916.

R2916

229° (10.4)

314° (9)

CEGEX

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (129°F).

SKIPP

101°

230K

281°

4 NM

HOLD 4000 1600

KEY WEST EYW

56

183° (9.6)

1600

KEY WEST INTL

94

85

RW04

196

BIPIN

1600 248° (26.4)

037°

(FAF) MEDAC

1600 038° (5)

4 NM

238°

230K

058°

(IF/IAF) TAVDE

HOLD 4000 1600

MSA RW04 25 NM

15,000

CONTIGUOUS US ADIZ

EMERG SAFE ALT 100 NM 15,000

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 35).

1600 CEGEX

4 NM Holding Pattern

4000 1600

238°

058°

TAVDE

038°

MEDAC

037°

1.3 NM to RW04

RW04

1600

GP 3.00° TCH 45

4.9 NM

ELEV 6

TDZE 4

127

22

14

10,001 x 200

92

47

BCN TWR

8

A1

7000 x 150

7001 x 150

4

32

037°

HIRL all rwys

CATEGORY	A	B	C	D
LNAV/VNAV DA	245-¾	250	(300-¾)	
LNAV MDA	460-1 456	(500-1)	460-1⅜ 456	(500-1⅜)
C CIRCLING	460-1 454 (500-1)	500-1 494 (500-1)	500-1½ 494 (500-1½)	560-2 554 (600-2)

KEY WEST, FLORIDA

Amdt 2 23FEB23

24°34'N - 81°41'W KEY WEST NAS (BOCA CHICA FLD) (KNQX)

RNAV (GPS) RWY 4

SE-3, 10 JUL 2025 to 07 AUG 2025