ILS or LOC RWY 7L

LOS ANGELES INTL (LAX)

LOC/DME I-IAS	APP CRS		7L	7R
111.1	071°	Rwy Ldg	11259	11095
Chan 48		TDZE	128	128
		Apt Elev	128	128

From FIM VORTAC: RNAV 1-GPS required. DME or RADAR required.

T Simultaneous approach authorized. Autopilot coupled approach NA below 925. Inop table does not apply to Sidestep Rwy 7R Cats A and B.

MALSR Rwy 7L

MALSR Rwy 7R

MISSED APPROACH: Climb to 3000 on LAX VORTAC R-068 to DOWNE INT/LAX 15.5 DME/RADAR and hold.

D-ATIS	SOCAL APP CON		LOS ANGELES TOWER	GND CON	CLNC DEL	CPDLC
ARR 133.8	124.3 363.2 (APCH FM WEST)	124.9 269.0 (090°-224°)	N 133.9 239.3	N 121.65 327.0	120.35	
DEP 135.65	124.5 235.975 (225°-044°)	128.5 360.7 (045°-089°)	S 120.95 379.1	S 121.75 327.0 W 121.4 327.0	327.0	





ELEV 128 D TDZE 7L 128 TDZE 7R 128



TDZ/CL Rwys 6R, 7L, 24R, and 25L
HIRL all Rwys

CATEGORY	A	B	C	D
S-ILS 7L	336/18 208 (300-½)			
S-LOC 7L	520/24 392 (400-½)		520/35 392 (400-⅝)	
SIDESTEP 7R	520/55 392 (400-1)			520-1½ 392 (400-1½)

FAF to MAP 5.1 NM

Knots	60	90	120	150	180
Min:Sec	5:06	3:24	2:33	2:02	1:42

SW-3, 10 JUL 2025 to 07 AUG 2025
SW-3, 10 JUL 2025 to 07 AUG 2025