

APP CRS	Rwy Ldg	9748
071°	TDZE	116
	Apt Elev	128

RNAV (RNP) Z RWY 6R

LOS ANGELES INTL (LAX)

▼

For uncompensated Baro-VNAV systems, procedure NA below 5°C (41°F) or above 54°C (130°F). GPS required. Simultaneous approach authorized. For inop ALS, increase RNP 0.30 all Cats visibility to RVR 6000.

MALSR

MISSED APPROACH: Climb to 3000 on track 071° to ZIMLO and on track 042° to AMTRA and hold.

D-ATIS	SOCAL APP CON	LOS ANGELES TOWER	GND CON	CLNC DEL	CPDLC
ARR 133.8	124.3 363.2	124.9 269.0	N 121.65 327.0	120.35	
DEF 135.65	124.5 235.975	128.5 360.7	S 121.75 327.0	327.0	
	(225°-044°)	(090°-224°)	W 121.4 327.0		
		(045°-089°)			

SW-3, 10 JUL 2025 to 07 AUG 2025

Procedure NA for arrivals at EXERT on V25 westbound and V27 northwest bound.

MSA RW06R 2.5 NM

7800

LOS ANGELES INTL (LAX)

ELEV 128

TDZE 116

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 69).

OTTES

GUPPI

3000

ZIMLO

AMTRA

tr 071°

tr 042°

△

3600

071°

1800

RW06R

GP 3.00°

TCH 53

6 NM

5.1 NM

CATEGORY	A	B	C	D
RNP 0.30	DA	471/40	355 (400-¾)	

AUTHORIZATION REQUIRED

TDZ/CL Rwy 6R, 7L, 24R, and 25L

HIRL all Rwy

LOS ANGELES, CALIFORNIA

Amcl 1 10NOV16

33°57'N-118°24'W

LOS ANGELES INTL (LAX)

RNAV (RNP) Z RWY 6R