


WAAS CH 86421 W28A	APP CRS 282°	Rwy Idg TDZE 430 Apt Elev 437
----------------------------------------	------------------------	---------------------------------------------------

RNAV (GPS) RWY 28

MACON DOWNTOWN (MAC)

RNP APCH-GPS.		MISSED APPROACH: Climb to 3000 direct HAVIM and hold.
Baro-VNAV NA. Rwy 28 helicopter visibility reduction below ¾ SM NA. Use Middle Georgia altimeter setting, when not received, use Robbins AFB altimeter setting and increase LPV DA to 726 feet, increase LNAV/VNAV DA to 1063 feet and increase all MDAs 20 feet.		
MCN ASOS 120.775	ATLANTA APP CON ★ 124.2 279.6	UNICOM 123.0 (CTAF) 0



ELEV 437	D	TDZE 430
-----------------	----------	-----------------

3000 HAVIM		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00°/TCH 23).	
*LNAV only.		4 NM Holding Pattern	
RW28		JOBRA	
WURAS 2.6 NM to RW28		HONKA 2100	
*1280		2100	
2.6 NM		6.5 NM	
CATEGORY	A	B	C
LPV DA	712-1	282 (300-1)	
LNAV/VNAV DA	1049-2½	619 (700-2½)	
LNAV MDA	980-1 550 (600-1)	980-1½ 550 (600-1½)	
CIRCLING	1200-1 763 (800-1)	1320-2¾ 883 (900-2¾)	1480-3 1043 (1100-3)

MIRL Rwy 10-28 0