

WAAS CH <b>87029</b> <b>W03A</b>	APP CRS <b>032°</b>	Rwy Idg TDZE <b>860</b> Apt Elev <b>887</b>	<b>6769</b> <b>860</b> <b>887</b>
--	------------------------	---	---


RNAV (GPS) RWY 3

DANE COUNTY RGNL/TRUAX FLD (MSN)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C (-4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA.

MISSED APPROACH: Climb to 3600 direct FONUV and hold.

ATIS <b>124.65 278.3</b>	MADISON APP CON ★ <b>135.45 343.7</b>	MADISON TOWER ★ <b>119.3 (CTAF) 0 257.8</b>	GND CON <b>121.9 348.6</b>	CLNC DEL <b>121.625</b>	UNICOM <b>122.95</b>
-----------------------------	--	--	-------------------------------	----------------------------	-------------------------



4 NM Holding Pattern		3600 FONUV	
WIROD		*LNAV only	
3600 ← 212°		ZUSNA	
032° →		ZEPUD	
032°		MIBPU 2 NM to RW03	
2700		*1.3 NM to RW03	
2600		*1540	
GP 3.00°			
TCH 49			
CATEGORY	A	B	C
LPV DA	1060-¾	200 (200-¾)	
LNAV/VNAV DA	1179-1	319 (300-1)	
LNAV MDA	1320-1	460 (500-1)	1320-1¾ 460 (500-1¾)
CIRCLING	1420-1 533 (600-1)	1460-1 573 (600-1)	1460-1½ 573 (600-1½) 1700-2¾ 813 (900-2¾)

