


WAAS CH 97507 W18D	APP CRS 180°	Rwy Idg TDZE Apt Elev	11120 290 341
--	------------------------	-----------------------------	--

RNAV (GPS) Z RWY 18C
MEMPHIS INTL (MEM)

<p>RNP APCH - GPS.</p> <p>T Simultaneous approach authorized. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. Use of FD or AP required during simultaneous operations. LNAV procedure NA during simultaneous operations. For Inop ALS, increase LPV all Cats visibility to RVR 5500 and LNAV/VNAV all Cats visibility to 1% SM.</p>	<p>MALSR</p> 	<p>MISSED APPROACH: Climb to 5000 direct CEDEN and on track 137° to KEEZE and hold, continue climb-in-hold to 5000.</p>
---	--	---

MEMPHIS APP CON		MEMPHIS TOWER		GND CON		CLNC DEL
119.1	291.6 (176°-355°)	(Rwy 9-27)	118.3 257.8	(Rwy 9-27)	121.0 379.2	
125.8	338.3 (356°-175°)	(Rwys 18C-36C, 18L-36R)	119.7 257.8	(Rwys 18C-36C, 18L-36R)	121.9 379.2	
		(Rwy 18R-36L)	128.425 257.8	(Rwy 18R-36L)	121.65 379.2	

D-ATIS 127.75	HOLD 6000 3900	CPDLC
-------------------------	-------------------	-------

