

MIAMI DEP CON  
119.45 290.325  
BEECH, BNGOS, DORRL,  
GO, FOIZL, HURCN, ZFF)  
125.5 354.1  
(GWAVA, KETIL, MAYNR)  
ATIS  
125.9  
CLNC DEL  
119.2  
GND CON  
120.025  
OPA LOCKA TOWER ★  
134.675 (CTAF)

FREEPORT  
113.2 ZFP : : : :  
Chan 79

BIMINI  
116.7 ZBV  
Chan 114

1300  
(24)

**TAKEOFF MINIMUMS**  
Rwys 9L/R, 12, 27L/R, 30: Standard.

(CONTINUED ON FOLLOWING PAGE)

**TOP ALTITUDE: AS  
ASSIGNED BY ATC**

PALM BEACH  
115.7 PBI  
Chan 104

FORT LAUDERDALE  
114.4 FLL ::::  
Chan 91

VIRGINIA KEY  
117.1 VKZ   
Chan 118

GWAVA

RADAR and DME required.

**SPECIAL INSTRUCTIONS**  
Unless otherwise assigned, use departure frequency depicted associated with the transition in clearance.

NOTE: Turboprops operate in a manner that will result in best forward speed and climb rate.

NOTE: File DP in remarks section of flight plan.

NOTE: Chart not to scale.

MIAMI-OPA LOCKA EXEC (OPF)