

APP CRS	Rwy Ldg	9487
316°	TDZE	578
	Apt Elev	599

RNAV (RNP) Z RWY 31
NASHVILLE INTL (BNA)

For uncompensated Baro-VNAV systems, procedure NA below -16°C (4°F) or above 54°C (130°F). GPS required.

MISSED APPROACH: Climb to 3100 on track 316° to JARAS and hold.

D-ATIS
135.1

NASHVILLE APP CON
118.4 360.7

NASHVILLE TOWER
118.6 257.8

GND CON
121.9 348.6

CLNC DEL
126.05

CPDLC

MISSED APCH FIX

RADAR REQUIRED

Λ 1208

Λ 1035

(IF) \leftarrow
GILME
5000 210K
(RF REQD)

1476
A

$$\begin{array}{r} \text{(IF)} \\ \text{BGEDD} \\ \hline 4000 \quad 210K \\ \hline \text{(RF REQD)} \end{array}$$

40

(IF) \rightarrow
ONUGE
4000
(RNP 0.50)

ELEV 599	D	TDZE 578
----------	----------	----------

D TDZE 578

HIRL all Rwy's
TDZ/CL Rwy's 2L and 2R
REIL Rwy's 13, 20C, and 31

3100

316

JARAS

See planview for multiple IF locations.

COVBI
|
1700
|

GP 3.00°
TCH 52

CATEGORY
RNP 0.25 DA
RNP 0.30 DA

A	

B	C
1025-1 $\frac{1}{2}$	447 (500-1 $\frac{1}{2}$)
1099-1 $\frac{3}{4}$	521 (600-1 $\frac{3}{4}$)

D

AUTHORIZATION REQUIRED

RNAV (RNP) Z RWY 31