

WAAS CH 49013 W20D	APP CRS 201°	Rwy Ldg TDZE 551 Apt Elev 599
--	------------------------	---

RNAV (GPS) Y RWY 20L

NASHVILLE INTL (BNA)



⚠

For uncompensated Baro-VNAV systems, procedure NA below -11°C (13°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Simultaneous approach authorized with Rwy 20R. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations. For inop MALSR, increase LNAV/VNAV all Cats visibility to 1%. ** RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH:
Climb to 1300 then climbing left turn to 4000 direct CENOP and hold.

D-ATIS 135.1	NASHVILLE APP CON 118.4 360.7	NASHVILLE TOWER 118.6 257.8	GND CON 121.9 348.6	CLNC DEL 126.05	CPDLC
------------------------	---	---------------------------------------	-------------------------------	---------------------------	-------



1300 ↑	4000 ↖	CENOP △	WAYLN 4 NM Holding Pattern			
*LNAV only.			JUDD 2000	201°		021° → ← 201° 3000
RW20L 1.2 NM to RW20L			XIYRI 2 NM to RW20L	201°		GP 3.00° TCH 47
1.2 NM			0.8 NM	2.4 NM	6.2 NM	
CATEGORY		A	B	C	D	
LPV DA		** 751/24 200 (200-½)				
LNAV/ VNAV		DA 1025/58 474 (500-1¼)				
LNAV MDA		980/24	429 (400-½)	980/40	429 (400-¾)	
CIRCLING		1100-1 501 (600-1)	1120-1 521 (600-1)	1200-1¾ 601 (700-1¾)	1380-2½ 781 (800-2½)	