LOC/DME I-INB	APP CRS	Rwy Ldg	10000
108.7	296°	TDZE	9
Chan 24		Apt Elev	9

ILS RWY 30 (SA CAT I)

OAKLAND INTL (OAK)

RNP APCH - GPS. From FFIST or MYSHN.

DME or RADAR required.

Requires specific OPSPEC, MSPEC, or LOA approval. Missed approach requires minimum climb of 213 feet per NM to 1540, if unable to meet climb gradient, see ILS or LOC RWY 30.

ALSF-2

MISSED APPROACH: Climb to 600 then climbing left turn to 4000 on heading 260° and on SAU VOR/DME R-110 to SAU VOR/DME and hold, continue climb-in-hold to 4000.

D-ATIS	NORCAL APP CON	OAKLAND TOWER	GND CON	CLNC DEL	CPDLC
133.775	125.35 263.15	118.3 291.65 (Rwys 10L/R-28L/R, 15-33) 127.2 256.9 (Rwy 12-30)	121.9 (Rwys 10L/R-28L/R, 15-33) 121.75 (Rwy 12-30)	121.1	

MISSED APCH FIX

035° 215° R-035

SAUSALITO SAU 116.2 Chan 109

ALTERNATE MISSED APCH FIX

R-300 120° 300°

OAKLAND OAK 116.8 Chan 115

2025 3902 1974 1243± 1619 2212 731± 394± 202 2016 947 156 831± 1575± 1805 2328

OAKLAND 116.8 OAK Chan 115

SAU R-110

LOCALIZER 108.7 I-INB Chan 24

MSA OAK 25 NM

170° 3800 5100 350°

296° 2000 296° (2.2) 2700 264° (3) 3500 254° (3.5) 238 MITOE I-INB 8.3 RADAR (IF) ZOLUM 4500 256° (6.1) PRFCT 6000 251° (6.3) (IAF) FFIST 9000 200K 7000

WUVON I-INB 10.5 RADAR 200K 2700 296° (5.1) PARBB 4500 4400 264° (4.8) FRNNY 116° 5000 264° (6) MYCAF (IAF) MYSHN 6200

3049

ELEV 9 D TDZE 9

15 33 10L 10R 28L 28R 12 TWR 3576 X 75 5457 X 150 6213 X 150 10520 X 150

REIL Rwy 10R
TDZ/CL Rwy 30
MIRL Rwy 15-33
HIRL Rwys 12-30, 10L-28R, 10R-28L

600	4000 hdg 260°	SAU R-110	SAU

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 71).

MITOE I-INB 8.3 RADAR 2000

WUVON I-INB 10.5 RADAR 2700

296° 2000

GS 3.00° TCH 55

1051' 6.1 NM 2.2 NM

CATEGORY	A	B	C	D
S-ILS 30	RA 150/14 150 DA 159			

SA CATEGORY I ILS - SPECIAL AIRCREW & AIRCRAFT CERTIFICATION REQUIRED

SW-2, 10 JUL 2025 to 07 AUG 2025
SW-2, 10 JUL 2025 to 07 AUG 2025