




WAAS CH 70306 W11A	APP CRS 110°	Rwy Idg TDZE 76 Apt Elev 76	7200
--	------------------------	---	-------------

RNAV (GPS) RWY 11
PORTLAND INTL JETPORT (PWM)

RNP APCH - GPS.			ALSF-2	MISSED APPROACH: Climb to 3000 direct SAPPE and hold, continue climb-in-hold to 3000.		
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C or above 54°C.						
ATIS 119.05	PORTLAND APP CON ★ 119.75 269.35	PORTLAND TOWER ★ 120.9 0 (CTAF) 257.8	GND CON 121.9	CLNC DEL 121.9	UNICOM 122.95	



CATEGORY	A	B	C	D
LPV DA	276/18 200 (200-½)			
LNAV/VNAV DA	456/40 380 (400-¾)			
LNAV MDA	520/24 444 (500-½)	520/45 444 (500-¾)		
CIRCLING	620-1 544 (600-1)	640-1 564 (600-1)	740-1¾ 664 (700-1¾)	860-2½ 784 (800-2½)



NE-1, 10 JUL 2025 to 07 AUG 2025

NE-1, 10 JUL 2025 to 07 AUG 2025