

ALAMO FOUR DEPARTURE

RADAR required.

TOP ALTITUDE:
ASSIGNED BY ATC

SAN ANTONIO DEP CON
125.7 290.225
ATIS
128.8
CLNC DEL (When twr closed)
121.7
GND CON
121.7 379.9
STINSON TOWER ★
118.2 379.9

COWBOY
116.2 CVE
Chan 109


GOOCH SPRINGS
112.5 AGJ
Chan 72

CENTEX
112.8 CWK
Chan 75

STONEWALL
113.8 STV
Chan 85

BROWNWOOD
113.55 BWD
Chan 82 (Y)

SAN ANTONIO
116.8 SAT
Chan 115



NOTE: GOBBY Transition: Right turn at GOBBY NA for ACFT REQ FL240 and ABV.
NOTE: HENLY Transition: Right turn at HENLY NA for ACFT REQ FL240 and ABV.

TAKEOFF MINIMUMS

Rwy 14, 32: Standard.

Rwy 9: Standard with minimum climb of 230'/NM to 1900.
Rwy 27: 300-1% or standard with minimum climb of 225'/NM to 900, or alternatively, with standard takeoff minimums and a normal 200'/NM climb gradient, takeoff must occur no later than 1800' prior to DER.

SC-3, 10 JUL 2025 to 07 AUG 2025

SC-3, 10 JUL 2025 to 07 AUG 2025

(CONTINUED ON FOLLOWING PAGE)

NOTE: Chart not to scale

ALAMO FOUR DEPARTURE