

LOC I-SCH 109.7	APP CRS 040°	Rwy Idg TDZE Apt Elev	7001 338 378
---------------------------	------------------------	-----------------------------	---

ILS or LOC RWY 4

SCHENECTADY COUNTY (SCH)

<div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div>NA</div></div><div>Circling Rwy 10 NA at night. Inop table does not apply to S-ILS 4. For inop MALSRL, increase S-LOC 4 Cat A/B visibility to 1 mile and Cat C/D visibility to 1½ mile. For inoperative MALSRL when using Albany altimeter setting, increase S-LOC 4 Cat A/B visibility to 1 mile. When using Albany altimeter setting inoperative table does not apply to S-ILS-4. ADF required. When local altimeter setting not received, use Albany altimeter setting and increase all DA 33 feet, and all MDA 40 feet. Helicopter visibility reduction below ¾ SM NA.</div></div>			<div>MALSRL</div> <div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div>AG</div></div>	<div>MISSED APPROACH:</div> <div>Climb to 1500 on 040° course and on HEU NDB bearing 045° then climbing right turn to 3700 direct HEU NDB and hold, continue climb-in-hold to 3700.</div>
<div>AWOS-3</div> <div>119.275</div>	<div>ALBANY APP CON</div> <div>132.825 263.075</div>	<div>SCHENECTADY TOWER ★</div> <div>121.3 (CTAF) 0 321.1</div>	<div>GND CON</div> <div>121.9</div>	<div>UNICOM</div> <div>122.95</div>

