

LOC I-FSD 109.9	APP CRS 030°	Rwy Idg TDZE Apt Elev	8999 1424 1430
---------------------------	------------------------	-----------------------------	---

ILS or LOC RWY 3

JOE FOSS FLD (FSD)

T

A

ASR

-31°C

MAISLR

MISSED APPROACH: Climb to 3400 then left turn direct FSD VORTAC and hold.

ATIS
126.6

SIoux FALLS APP CON *
125.8 284.725

SIoux FALLS TOWER *
118.3 (CTAF) 0 257.8

GND CON
121.9 348.6

UNICOM
122.95

ADF or RADAR REQUIRED

SIoux FALLS 115.0 FSD Chan 97

LOCALIZER 109.9 I-FSD

LOM/IAF ROKKY 245 FS RADAR

ALTERNATE MISSED APCH FIX ROKKY 245 FS RADAR

MSA FS 25 NM

One Minute Holding Pattern		FS LOM RADAR	3400	FSD	ELEV 1430	TDZE 1424
		MAREY INT	*LOC only		REIL Rwy 15 and 33	
GS 300° TCH 54		4.3 NM	1.4 NM		HIRL Rwy 3-21 and 15-33	
CATEGORY	A	B	C	D	MIRL Rwy 9-27	
S-ILS 3	1674/24 250 (300-½)				TDZ/CL Rwy 3	
S-LOC 3	1940/24	516 (600-½)	1940/55	516 (600-1)		
CIRCLING	1960-1 530 (600-1)	1980-1 550 (600-1)	2060-1¾ 630 (700-1¾)	2200-2½ 770 (800-2½)		
MAREY FIX MINIMUMS (DUAL VOR RECEIVERS REQUIRED)						
S-LOC 3	1800/24	376 (400-½)	1800/35	376 (400-¾)		
CIRCLING	1960-1 530 (600-1)	1980-1 550 (600-1)	2060-1¾ 630 (700-1¾)	2200-2½ 770 (800-2½)		
					FAF to MAP 5.7 NM	
					Knots	60 90 120 150 180
					Min:Sec	5:42 3:48 2:51 2:17 1:54

SIoux FALLS, SOUTH DAKOTA

Amdt 27G 18JUN20

43°35'N-96°45'W

JOE FOSS FLD (FSD)

ILS or LOC RWY 3