


WAAS Ch 49199 W31A	APP CRS 310°	Rwy Idg 4559 TDZE 390 Apt Elev 390
--	------------------------	---

RNAV (GPS) RWY 31

TEXARKANA RGNL-WEBB FLD (TXK)

RNP APCH-GPS. ▼ Rwy 31 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use De Queen altimeter setting and increase all DA/MDA 100 feet, increase LPV and LNAV/VNAV all Cats, and LNAV Cat C and D visibility ¼ SM, and Circling Cat C and D visibility ¼ SM. Baro-VNAV and VDP NA when using De Queen altimeter setting. ▲	MISSED APPROACH: Climb to 2000 direct JELGA and hold.
---	--

ATIS 120.2	FORT WORTH CENTER 123.925 269.475	TEXARKANA TOWER★ 123.875 (CTAF) 0 235.625	GND CON 119.225
----------------------	---	---	---------------------------



2000	JELGA				
↑	✧				
RW31		DAXPO		WATLE	
1.6 NM to RW31		1.6 NM		3.3 NM	
310°		130°		2000	
2000		4 NM Holding Pattern		GP 3.00° TCH 39	
CATEGORY	A	B	C	D	
LPV DA	645-1 255 (300-1)				
LNAV/VNAV DA	707-1¼ 317 (400-1¼)				
LNAV MDA	920-1 530 (600-1)	920-1½ 530 (600-1½)	920-1¾ 530 (600-1¾)		
CIRCLING	920-1 530 (600-1)	1000-1¾ 610 (700-1¾)	1080-2¼ 690 (700-2¼)		

MIRL Rwy 13-31 0
HIRL Rwy 4-22 0