


WAAS CH 50344 W36B	APP CRS 360°	Rwy Idg TDZE Apt Elev	5101 678 678
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 36L
TULSA INTL (TUL)

RNP APCH - GPS.		MISSED APPROACH: Climb to 3500 direct AXIWU and hold.	
Use of FD or AP required during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -14°C or above 54°C. Simultaneous approach authorized. LNAV procedure NA during simultaneous operations.			
D-ATIS 124.9 377.2	TULSA APP CON 124.0 338.3	TULSA TOWER 121.2 310.8 (Rwys 18L-36R, 8-26) 118.7 257.8 (Rwy 18R-36L)	CLNC DEL 134.05 284.7
		GND CON 121.9 348.6	



30 NM to SUSNE (NoPT)

HOLD 17500 3600

4 NM Holding Pattern

SUSNE

PASIE

TREEO 1.7 NM to RW36L

RW36L

17500 3600

180°

360°

360°

2400

2400

1260

6.9 NM

3.6 NM

1.7 NM

GP 3.00° TCH 45

3500

AXIWU

CATEGORY	A	B	C	D
LPV DA	928- $\frac{3}{4}$		250 (300- $\frac{3}{4}$)	
LNAV/VNAV DA	1088-1 $\frac{1}{8}$		410 (500-1 $\frac{1}{8}$)	
LNAV MDA	1120-1	442 (500-1)	1120-1 $\frac{3}{8}$	442 (500-1 $\frac{3}{8}$)
CIRCLING	1120-1 442 (500-1)	1160-1 482 (500-1)	1500-2 $\frac{1}{2}$ 822 (900-2 $\frac{1}{2}$)	1520-2 $\frac{3}{4}$ 842 (900-2 $\frac{3}{4}$)

ELEV 678

TDZE 678

TDZ/CL Rwy 36R

HIRL All Rwys

REIL Rwys 8, 18R and 36L

18L

18R

36L

36R

TWR 809

0.4% UP

0.2% UP

0.5% UP

10000 X 150

7376 X 150

360°