RNAV (RNP) Z RWY 32

PALM BEACH INTL (PBI)

APP CRS	Rwy Ldg	6513
321°	TDZE	16
	Apt Elev	20

RNP AR APCH - GPS.

For uncompensated Baro-VNAV systems, procedure NA below 6°C or above 54°C.

MISSED APPROACH: Climb to 3000 direct FOMID and on track 005° to MORGA and hold.

D-ATIS	PALM BEACH APP CON	PALM BEACH TOWER	GND CON	CLNC DEL	CPDLC
123.75	128.3 317.4	119.1 257.8	121.9 284.6	121.6 284.6	

MISSED APCH FIX

MORGA

163° 343° 4 NM

005° (11.1)

FOMID

506 536 439 206 167± 118 434 1552

RW32

321° (4.5)

(IAF) HETMO 4000 210K

3500 80° (3.6)

(IF) KARRL

3500 180° (4.6)

PALLM

1500 (7.4)

(FAF) RUMDE

1500 321° (3)

REEEL

2400 321° (4.5)

(IF) LIDRE 3000

2400 (6.11)

COBAC

4300 120° (2.6)

(IF) BEKAH 6000 210K

5000 120° (7)

QATHY

MSA RW32 25 NM 2600

ELEV 20 D TDZE 16

3000 FOMID tr 005° MORGA

VGSI and RNAV glidepath not coincident (VGSI Angle 3.25/TCH 57).

RUMDE 1500

321° 1500

RW32

See planview for multiple IF locations.

GP 3.00° TCH 57

4.5 NM

CATEGORY	A	B	C	D
RNP 0.11 DA		322-⅞	306 (400-⅞)	
RNP 0.30 DA		376-1	360 (400-1)	

AUTHORIZATION REQUIRED



HIRL Rwy 10L-28R
REIL Rwys 10R, 14, 28L, 28R and 32
MIRL Rwys 14-32 and 10R-28L

SE-3, 10 JUL 2025 to 07 AUG 2025
SE-3, 10 JUL 2025 to 07 AUG 2025