WICHITA, KANSAS

RNAV (RNP) Z RWY 19R

APCH CRS	Rwy ldg	12,000
188°	TDZE	1372
	Arpt Elev	1372

(USAF) MC CONNELL AFB (KIAB)

RNP AR APCH-GPS

* When ALS inop, increase vis to 1 1/4 miles.
** When ALS inop, increase vis to 1 3/8 miles.

ALSF-1

MISSED APPROACH: Climb to 4000 direct HOKET and hold as published. Expect further clearance from ATC.

D-ATIS	WICHITA APP CON	TOWER	GND CON
124.65 269.9	134.8 269.1	127.25 291.775	118.0 275.8

For uncompensated Baro-VNAV systems, procedure not authorized below -17°C. or above 54°C.

AUTHORIZATION REQUIRED

(IF/IAF) WITBA 4000

3000 189° (9)

(10.5)

JABSO

COLONEL JAMES JABARA

(FAF) FOVEL

3000 198° (1.1)

GATLE

188°

BEECH FACTORY

1478

RW19R

CESSNA ACFT FIELD

4000 003° (5.6)

(IF/IAF) KOSAC 4000

188° (16.1)

RADAR required for holding above 5000 or above 230 KIAS

HOKET

HOLD 6000 4000

008° 188° 200K

4 NM

MSA RW19R 25 NM

3600

EMERG SAFE ALT 100 NM 4000

4000 tr 188° HOKET

See planview for multiple IF locations

FOVEL 3000

3000

RW19R

188°

GP 3.00° TCH 56

4.9 NM

ELEV 1372 TDZE 1372

188°

TWR

0.3% DOWN 12,000 x 150

12,007 x 150

19L 19R

1L 1R

HIRL all rwys

CATEGORY	A	B	C	D
RNP 0.10 DA*	1798/40		426	(500-¾)
RNP 0.30 DA**	1844/50		472	(500-1)

NC-2, 10 JUL 2025 to 07 AUG 2025
NC-2, 10 JUL 2025 to 07 AUG 2025