

LOC I-GMX	APP CRS	Rwy Idg	8016
111.55	238°	TDZE	26
		Apt Elev	32

ILS Y or LOC RWY 24

WILMINGTON INTL (ILM)

**RVR 1800 authorized with use of FD or AP or HUD to DA.

ADF required.

MALSR

MISSED APPROACH: Climb to 500 then climbing right turn to 1800 direct WILZE LOM and hold.

ATIS	WILMINGTON APP CON★	WILMINGTON TOWER★	GND CON	CLNC DEL	UNICOM
124.975	118.25 284.65 (164°-343°) 135.75 317.425 (344°-163°)	119.9 (CTAF) 0 239.3	121.9 348.6	120.875	122.95


ALTERNATE MISSED APCH FIX

AIRLI

IL : - . .

281

RNAV 1-GPS or RADAR REQUIRED



ELEV 32 TDZE 26

238°

775X150

87

8016 X 100

TWR 136

35

HIRL Rwy 6-24 and 17-35

REIL Rwy 6 and 17

FAF to MAP 5.3 NM

Knots	60	90	120	150	180
Min:Sec	5:18	3:32	2:39	2:07	1:46

CATEGORY			
A		B	
S-ILS 24**		226/24 200 (200-½)	
S-LOC 24		500/24 474 (500-½)	500/50 474 (500-1)
CIRCLING		560-1 528 (600-1)	720-2 688 (700-2) 920-3 888 (900-3)