

APP CRS
274°

Rwy Idg
TDZE
1068

Apt Elev
1099

RNAV (RNP) Y RWY 27

YAKIMA AIR TRML/MCALLISTER FLD (YKM)

RNP APCH - GPS. From MUDE or OVTEE or YIGUN: RF.

▼ For uncompensated Baro-VNAV systems, procedure NA below -15°C or above 54°C. DATVE transition NA when R-6714 A, C, D active. For inop ALS, increase RNP 0.30* all Cats visibility to RVR 5500 and RNP 0.30 all Cats to 2½ SM.

MALSR

MISSED APPROACH: Climb to 5100 on track 274° to PUBBO left turn to SIBSY and on track 097° to MUDE and hold.

*Missed approach requires minimum climb of 425 feet per NM to 3400.

ATIS 125.25	SPOKANE APP CON* 123.8 263.15	YAKIMA TOWER* 133.25 (CTAF) 0 257.8	GND CON 121.9	CLNC DEL 121.9	UNICOM 122.95
----------------	----------------------------------	--	------------------	-------------------	------------------

ELEV 1099

TDZE 1068

MIRL Rwy 4-22

HIRL Rwy 9-27

REIL Rwy 4, 9, and 22

5100 PUBBO

tr 274°

SIBSY

MUDE

tr 097°

OAKSS

2900

See planview for multiple IF locations.

GP 3.00°

TCH 57

5.6 NM

274°

2900

5100 PUBBO

tr 274°

SIBSY

MUDE

tr 097°

OAKSS

2900

See planview for multiple IF locations.

GP 3.00°

TCH 57

5.6 NM

274°

2900

CATEGORY	A	B	C	D
RNP 0.30 DA*	1418/30	350 (400-5%)		
RNP 0.30 DA	1845-13¼	777 (800-1¼)		

AUTHORIZATION REQUIRED

YAKIMA, WASHINGTON

YAKIMA AIR TRML/MCALLISTER FLD (YKM)

Orig-D 23FEB23

46°34'N-120°33'W

RNAV (RNP) Y RWY 27