

WAAS CH <b>42629</b> <b>W13A</b>	APP CRS <b>128°</b>	Rwy Idg TDZE Apt Elev	<b>5997</b> <b>178</b> <b>178</b>
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 13

ALICE INTL (ALI)

RNP APCH.


▼

⚠

Baro-VNAV NA when using Nueces County altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -3°C or above 42°C. When local altimeter setting not received, use Nueces County altimeter setting and increase all DA 56 feet and all MDA 60 feet, increase LPV and LNAV/VNAV visibility all Cats ¼ mile and LNAV Cat C and D ½ mile. Rwy 13 helicopter visibility reduction below ¾ SM NA. VDP NA with Nueces County altimeter setting.

MISSED APPROACH: Climb to 2600 direct ITDAZ and hold.

ASOS <b>119.225</b>	KINGSVILLE APP CON ★ <b>119.9 290.45</b>	UNICOM <b>123.0 (CTAF) 0</b>
------------------------	---	---------------------------------



4 NM Holding Pattern		UWAGO		2600	ITDAZ
2100		← 308°	→ 128°	1900	WACBI 1900
GP 3.00° TCH 50		128°	1900	860	KOVLE 2 NM to RW13
					*1 NM to RW13
					RW13
					*LNAV only.
CATEGORY	A	B	C	D	
LPV DA		428-¾	250 (300-¾)		
LNAV/VNAV DA		428-¾	250 (300-¾)		
LNAV MDA	560-1	382 (400-1)	560-1½	382 (400-1½)	

