RNAV (GPS) RWY 9
BISHOP INTL (FNT)

WAAS CH 45714 W09A	APP CRS 094°	Rwy ldg 7201 TDZE 771 Apt Elev 782

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. For inop ALS, increase LNAV Cat C/D visibility to 1⅜ SM.
**RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 3000 direct JUBUG and on track 099° to KATTY and hold.

ATIS	GREAT LAKES APP CON ★	FLINT TOWER ★	GND CON	CLNC DEL	UNICOM
133.15	118.8 257.9	126.3 (CTAF) L 257.9	121.9	121.75	122.95



ELEV 782	D	TDZE 771



CATEGORY	A	B	C	D
LPV DA **	971/24 200 (200-½)			
LNAV/VNAV DA	1227/50 456 (500-1)			
LNAV MDA	1260/24 489 (500-½)		1260/50 489 (500-1)	
C CIRCLING	1260-1 478 (500-1)	1300-1 518 (600-1)	1300-1½ 518 (600-1½)	1520-2¼ 738 (800-2¼)

HIRL Rwys 9-27 and 18-36 L
REIL Rwy 18 and 36 L

EC-1, 10 JUL 2025 to 07 AUG 2025
EC-1, 10 JUL 2025 to 07 AUG 2025