LOC I-RDG	APP CRS	Rwy Idg	5151
109.5	004°	TDZE	343
		Apt Elev	344

ILS or LOC RWY 36

READING RGNL/CARL A SPAATZ FLD (RDG)

Night Landing: Rwy 18, 31 NA. Inoperative table does not apply. When local altimeter setting not received, use Harrisburg Intl altimeter setting and increase S-ILS 36 DA to 686 feet and all Cats visibility ¼ SM, and increase all MDAs 100 feet, and S-LOC 36 Cats C and D and Circling Cats B and C visibility ¼ SM.

MALSF

MISSED APPROACH: Climb to 3000 on heading 004° and RAV VORTAC R-114 to DUMMR INT/RAV 22.9 DME and hold, continue climb-in-hold to 3000.

ATIS	HARRISBURG APP CON	READING TOWER ★	GND CON	UNICOM
127.1	125.15 257.9	119.9 (CTAF) L 288.3	121.9	122.95







CATEGORY	A	B	C	D
S-ILS 36	593-1 250 (300-1)			
S-LOC 36	820-1 477 (500-1)		820-1¼ 477 (500-1¼)	820-1½ 477 (500-1½)
CIRCLING	1020-1 676 (700-1)	1080-1 736 (800-1)	1280-2¾ 936 (1000-2¾)	1660-3 1316 (1400-3)

REIL Rwy 13 and 31 L
HIRL Rwys 13-31 and 18-36 L

FAF to MAP 4.7 NM

Knots	60	90	120	150	180
Min:Sec	4:42	3:08	2:21	1:53	1:34

NE-4, 10 JUL 2025 to 07 AUG 2025
NE-4, 10 JUL 2025 to 07 AUG 2025