

LOC/DME I-VAC

110.75

Chan **44** (Y)

APP CRS

006°

Rwy Ldg

8000

TDZE

873

Apt Elev

896

ILS or LOC RWY 36L

CINCINNATI/NORTHERN KENTUCKY INTL (CVG)

RNP APCH - GPS. From FECTA or SPOOD or DAWGY or RUPPP or BRCAT.

DME or RADAR required. RADAR required for procedure entry at TMORE.

Simultaneous approach authorized. For inop ALS, increase S-LOC 36L Cat C and D visibility to RVR 5500.

ALS-F-2

MISSED APPROACH: Climb to 1300 then climbing left turn to 4000 on heading 260° and on FLM VOR/DME R-314 to JADRO/FLM 43.3 DME/RADAR and hold.

D-ATIS		CINCINNATI APP CON		CINCINNATI TOWER		GND CON	CINC DEL	CPDLC
ARR	DEP	119.7	363.15 (090°-269°)	118.975	360.85 (RWY 18L/36R)	121.7	127.175	
134.375	135.3	123.875	363.15 (270°-089°)	118.3 (RWYS 18C/36C, 09/27)				
				133.325 (RWY 18R/36L)				

BEPEE		ROPRR		JIMUR		IM	
I-VAC	11.3	I-VAC	6.4	I-VAC	3.1	I-VAC	1.5
RADAR		RADAR		RADAR		RADAR	
4000	006°	2500	1440	2500	1440	2500	1440
GS 3.00°		TCH 55		4.9 NM		3.3 NM	