

WAAS CH 82510 W07A	APP CRS 065°	Rwy Ldg TDZE Apt Elev	4784 319 331
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 7

WATERTOWN INTL (ART)

RNP APCH.

For inop ALS, increase LPV, LNAV/VNAV visibilities to ¾ SM and LNAV Cat C/D visibilities to 1¾ SM. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C or above 54°C.

MALSR

MISSED APPROACH: Climb to 900 then climbing left turn to 3500 direct NOYAQ and hold.

ASOS 132.325	KGTB ATIS 119.525	WHEELER-SACK APP CON 124.875 307.125	CLNC DEL 120.8	UNICOM 123.0 (CTAF) 0
------------------------	-----------------------------	--	--------------------------	--

ELEV	331	D	TDZE	319
------	-----	----------	------	-----

4 NM Holding Pattern

NOYAQ

3500

245°

065°

065°

NOYAQ

2000

9.9 NM

3.9 NM

1.3 NM

RW07

GP 3.00°

TCH 51

* LNAV only

900

3500

NOYAQ

01

0.3% UP

1999 X 150

7001 X 150

281

065°

CATEGORY	A	B	C	D
LPV DA	519-½ 200 (200-½)			
LNAV/VNAV DA	578-½ 259 (300-½)			
LNAV MDA	780-½	461 (500-½)	780-1	461 (500-1)
C CIRCLING	960-1	629 (700-1)	980-1¾ 649 (700-1¾)	1080-2½ 749 (800-2½)

HIRL Rwy 7-25 **0**

MIRL Rwy 10-28 **0**

WATERTOWN, NEW YORK

Amtd 3 19JUL18

44°00'N-76°01'W

WATERTOWN INTL (ART)

RNAV (GPS) RWY 7