RNAV (GPS) RWY 33

CAPE COD GATEWAY (HYA)

WAAS	APP CRS	Rwy Ldg	5105
CH 99423	336°	TDZE	50
W33A		Apt Elev	54

RNP APCH - GPS.

Baro-VNAV NA when using Chatham altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 43°C. When local altimeter setting not received, use Chatham altimeter setting: increase LPV DA to 332 feet; increase LNAV/VNAV DA to 393 feet; increase all MDAs 40 feet and visibility Cats C and D ¼ SM. Rwy 33 helicopter visibility reduction below ¾ SM NA. Circling Rwy 24 at night, operational VGSI required, remain on or above VGSI glidepath until threshold.

MISSED APPROACH: Climb to 2000 direct DUCEG and hold.

ATIS	BOSTON APP CON	HYANNIS TOWER ★	GND CON	CLNC DEL	CLNC DEL (When twr closed)	UNICOM
123.8	118.2 284.6	119.5 (CTAF) L 257.8	118.45	125.15	120.125	122.95



ELEV 54 D TDZE 50



REIL Rwy 6
HIRL Rwys 6-24 and 15-33 L

2000 DUCEG VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 53).



CATEGORY	A	B	C	D
LPV DA	300-1		250 (300-1)	
LNAV/VNAV DA	361-1		311 (400-1)	
LNAV MDA	620-1	570 (600-1)	620-1⅝	570 (600-1⅝)
C CIRCLING	620-1	566 (600-1)	860-2¼ 806 (900-2¼)	860-2½ 806 (900-2½)

NE-1, 10 JUL 2025 to 07 AUG 2025
NE-1, 10 JUL 2025 to 07 AUG 2025