

RNAV (GPS) RWY 24
DECATUR (DEC)

RNP APCH.


- ⚠** For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C.
⚠ Baro-VNAV and VDP NA when using Logan County altimeter setting.
⚠ When local altimeter setting not received, use Logan County altimeter setting; increase LPV DA to 1012 feet and visibility all Cats ¼ mile, LNAV/VNAV DA to 1168 feet and visibility all Cats ¼ mile; increase all MDA 80 feet and LNAV visibility Cats C/D ⅜ mile, Circling visibility Cats C/D ¼ mile.

MISSED APPROACH:
Climb to 2300 direct
FIKDO and hold.

FIKDO



060°
240°
4 NM

2300 ↑ 

*INAV only.

ZINOB 2.4 NM to RW24

PEDIC 2300

ZOLIP 4 NM Holding Pattern


2800

060° → ← 240°

RW24 1 NM

1 NM 1.4 NM 2.5 NM 6.1 NM

GP 3.00° TCH 52

CATEGORY		A	B	C	D
LPV	DA	932- ³ / ₄ 250 (300- ³ / ₄)			
LNAV/ VNAV	DA	1088-1 ³ / ₈ 406 (500-1 ³ / ₈)			
LNAV	MDA	1060-1 378 (400-1)			
 CIRCLING		1140-1 458 (500-1)	1240-1 558 (600-1)	1360-2 678 (700-2)	1360-2 ¹ / ₄ 678 (700-2 ¹ / ₄)