TOP ALTITUDE:
ASSIGNED BY ATC
RADAR and DME required.
LONE STAR DEP CON 124.3 282.275
ATIS 133.4
CLNC DEL 119.55
GND CON 121.6
ADDISON TOWER ★ 126.0 (CTAF) 239.0
TAKEOFF MINIMUMS
Rwy 34: Standard.
Rwy 16: 400-2½ or standard with minimum climb of 325'/NM to 1100.
MAVERICK 113.1 TTT Chan 78
FERRA
PODDE
MUZZO
KARYN
MILLSAP 117.7 MQP Chan 124
WICHITA FALLS 112.7 SPS Chan 74
LUBBOCK 109.2 LBB Chan 29
ABILENE 113.7 ABI Chan 84
V568
V66
V62
65
R-148
R-114
R-071
R-081
R-330
3100 328° (25)
4000 *3000 330° (22)
4000 *3000 285° (27)
2700 *2400 285° (37)
3500 *2800 250° (36)
3000 261° (13)
3700 253° (96)
6000 *4800 296° (127)
N
NOTE: LUBBOCK Transition: For all aircraft overflying the MQP VORTAC westbound or direct.
NOTE: MILLSAP Transition: For all aircraft overflying the MQP VORTAC westbound or direct.
NOTE: PODDE Transition: ATC assigned.
NOTE: WICHITA FALLS Transition: For all aircraft landing within the Wichita Falls terminal area or overflying the SPS VORTAC.
NOTE: For all aircraft requesting 17000 and below.
MSA TTT 25 NM
2700
090°
270°
3600
NOTE: Chart not to scale.
(CONTINUED ON FOLLOWING PAGE)