

WAAS CH 78311 W17A	APP CRS 172°	Rwy Idg 5900 TDZE 248 Apt Elev 250
--	------------------------	--

RNAV (GPS) RWY 17

CORVALLIS MUNI (CVO)

RNP APCH - GPS.

Circling Rwy 28 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, procedure NA. For inop ALS, increase LNAV Cat C/D visibility to 1¼ SM.

MALSR

MISSED APPROACH: Climb to 1100 then climbing left turn to 3700 direct INNOP and hold, continue climb-in-hold to 3700.

AWOS-3PT 135.775	CASCADE APP CON ★ 127.5 348.7	UNICOM 123.075 (CTAF) 1
----------------------------	---	--

Procedure NA for arrivals at CRAAF on V287 northeast bound.

• 2686

• 2096

• 4097

Procedure NA for arrivals at MAGOT on V23 northbound.

6000
3700

(IAF) CRAAF

3700 NoPT 111° (5.1)

4 NM (IAF) ADLOW

3700 NoPT 206° (3.7)

(IF/IAF) INNOP

2900 172° (3.9)

1757 EGBEW

2400 172° (2)

(FAF) ACVOL

Δ1741

Δ1316±

615±

3800 to INNOP 352° (12.8)

2.5 NM to RWY17

CAYJU

388

CORVALLIS CVO

380 Δ

3700 267° (10.6) MAGOT

MSA RW17 25 NM Δ1632

5300

ELEV 250	D	TDZE 248
----------	---	----------

172°

3100 X 75

5900 X 150

35

REIL Rwy 35 **1**

HIRL Rwy 17-35 **1**

MIRL Rwy 10-28 **1**

1100	3700	INNOP	INNOP	4 NM Holding Pattern
ACVOL	EGBEW	INNOP		
CAYJU 2.5 NM to RWY17	2400	2900	172°	352° 6000 3700
1.8 NM to RWY17	1080	2400	172°	GP 3.00° TCH 45
1.8 NM	0.7	4.1 NM	2 NM	3.9 NM
CATEGORY	A	B	C	D
LPV DA	448-½	200 (200-½)		
LNAV/VNAV DA	571-½	323 (400-½)		
LNAV MDA	880-½ 632 (700-½)	880-1⅜ 632 (700-1⅜)		
CIRCLING	880-1 630 (700-1)	920-1¾ 670 (700-1¾)	1080-2¾ 830 (900-2¾)	

CORVALLIS, OREGON
Amdt 1B 07OCT21

44°30'N-123°17'W

CORVALLIS MUNI (CVO)

RNAV (GPS) RWY 17

NW-1, 10 JUL 2025 to 07 AUG 2025

NW-1, 10 JUL 2025 to 07 AUG 2025