


D-ATIS 125.8  
CLNC DEL  
126.4 284.6  
CPDLC  
SAN JUAN TOWER  
132.05 257.8  
GND CON  
121.9 348.6  
SAN JUAN DEP CON  
119.4 269.2 (West & SW)  
120.9 290.2 (North & East)

TOP ALTITUDE:  
5000



TAKE-OFF MINIMUMS  
Rwy 8, 10: Standard. ATC climb of 230' per NM to 5000.  
Rwy 26, 28: NA-ATC.

NOTE: GPS required.  
NOTE: For Prop and Turboprop aircraft only.  
NOTE: RNAV 1.  
NOTE: RADAR required.

NOTE: Chart not to scale.



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 8: Climb heading 078° to 520, continue climb expect vectors to HAMAR, then via 095° track to NAILL. Thence. . . .

TAKEOFF RUNWAY 10: Climb heading 101° to 520, continue climb expect vectors to HAMAR, then via 095° track to NAILL. Thence. . . .

. . . . via assigned transition. Maintain 5000 unless assigned lower altitude. Expect clearance to FL280, or requested altitude if lower, ten minutes after departure.

JUICE TRANSITION (HAMAR2.JUICE)  
SLUGO TRANSITION (HAMAR2.SLUGO)  
ST. CROIX TRANSITION (HAMAR2.COY)