APP CRS	Rwy Ldg	8003
100°	TDZE	201
	Apt Elev	201

RNAV (GPS) RWY 10

LAKE CITY GATEWAY (LCQ)

RNP APCH - GPS.

Rwy 10 helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use GNV altimeter setting and increase all MDAs 100 feet, increase LNAV Cat C/D visibility ⅜ SM and Circling Cat C visibility ½ SM and Cat D ¼ SM. Straight-in Rwy 10 NA at night, Circling Rwy 5, 10, 23 NA at night.

MISSED APPROACH: Climb to 700 then climbing right turn to 2000 direct KRKLD and hold.

AWOS-3	JACKSONVILLE CENTER	LAKE CITY TOWER ★	GND CON	UNICOM
120.675	125.375 254.325	119.2 (CTAF) Ⓛ 314.6	121.9	122.95





CATEGORY	A	B	C	D
LNAV MDA	700-1	499 (500-1)	700-1⅜	499 (500-1⅜)
CIRCLING	760-1	559 (600-1)	780-1½ 579 (600-1½)	960-2½ 759 (800-2½)



REIL Rwys 10 and 28 Ⓛ
MIRL Rwys 5-23 and 10-28 Ⓛ

SE-3, 10 JUL 2025 to 07 AUG 2025
SE-3, 10 JUL 2025 to 07 AUG 2025