

APP CRS

Rwy Ldg

7257

133°

TDZE

35

Apt Elev

36

RNAV (RNP) Z RWY 13

VALLEY INTL (HRL)

RNP AR APCH - GPS.

For uncompensated Baro-VNAV systems, procedure NA below -1°C or above 54°C. When local altimeter setting not received, procedure NA.

MISSED APPROACH: Climb to 2000 direct AMAPE and hold.

|                |                               |   |                  |                  |
|----------------|-------------------------------|---|------------------|------------------|
| ATIS<br>124.85 | VALLEY APP CON<br>120.7 279.5 | HARLINGEN TOWER ★<br>119.3 (CTAF) 0 317.6 | GND CON<br>121.7 | UNICOM<br>122.95 |
|----------------|-------------------------------|---|------------------|------------------|

ELEV 36

D

TDZE 35

133°

81R

18L

TWR

9400 X 150

7257 X 150

5950 X 150

36R

36L

MIRL Rwy 18L-36R

REIL Rwy 13 and 18L

HRL Rwy 13-31 and 18R-36L

UNITED STATES

MEXICO

HUTES

1100

See planview for multiple IF locations.

2000

AMAPE

133°

RW13

GP 3.00°

TCH 59

3.2 NM

| CATEGORY    | A | B                                | C                                       | D |
|-------------|---|----------------------------------|---|---|
| RNP 0.15 DA |   | 285- <sup>3</sup> / <sub>4</sub> | 250 (300- <sup>3</sup> / <sub>4</sub> ) |   |
| RNP 0.30 DA |   | 342- <sup>7</sup> / <sub>8</sub> | 307 (400- <sup>7</sup> / <sub>8</sub> ) |   |

AUTHORIZATION REQUIRED

HARLINGEN, TEXAS

Amdt 1 11JUL24

26°14'N-97°39'W

VALLEY INTL (HRL)

RNAV (RNP) Z RWY 13