

WAAS
CH **45616**
W23A

APP CRS
233°

Rwy Idg
TDZE
Apt Elev
6215
931
947

RNAV (GPS) Y RWY 23
WEST VIRGINIA INTL YEAGER (CRW)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. For inoperative ALSF, increase LNAV/VNAV all Cnts visibility to 2¼. **RVR 1800 authorized with use of FD or AP or HUD to DA.

ALSF-1

ⓐ1

ⓐ1

MISSED APPROACH: Climb to 1400 then dimbing right turn to 3000 direct HVQ VOR/DME and hold.

ATIS 127.6	CHARLESTON APP CON 124.1 269.125	CHARLESTON TOWER 125.7 257.8	GND CON 121.8 348.6	CLNC DEL 118.55
----------------------	--	--	-------------------------------	---------------------------

ELEV **947**

D

TDZE **931**

HIRL Rwy 5-23

REIL Rwy 5

<div><div>1400</div><div>3000</div><div>HVQ</div></div>	<div><div>COSIK</div><div>ENIVY</div></div>	<div>6 NM Holding Pattern</div>		
<div><div>*LNAV only.</div><div><div><div><div>RW23</div><div>1.7 NM to RW23</div></div><div><div>1.7 NM</div><div>0.6 NM</div><div>2.2 NM</div><div>6.5 NM</div></div></div></div></div>	<div><div><div><div>2400</div><div>233°</div></div><div><div>2400</div><div>233°</div></div></div><div><div>GP 3.00°</div><div>TCH 56</div></div></div>			
CATEGORY	A	B	C	D
LPV	DA**	1131/24	200 (200-½)	
LNAV/VNAV	DA	1601-1⅞	670 (700-1⅞)	
LNAV	MDA	1500/24	569 (600-½)	1500-1⅓ 569 (600-1⅓)
CIRCLING		1600-1	653 (700-1)	1760-2½ 813 (900-2½) 1760-2¾ 813 (900-2¾)

CHARLESTON, WEST VIRGINIA

Amdt 1B 07DEC17

38°23'N-81°36'W

WEST VIRGINIA INTL YEAGER (CRW)

RNAV (GPS) Y RWY 23