

VORTAC ELW	APP CRS	Rwy Idg	6002
108.6	039°	TDZE	759
Chan 23		Apt Elev	782

VOR RWY 5

ANDERSON RGNL (A.ND)

▼

Rwy 17, 35 helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use CEU altimeter setting and increase all MDAs 60 feet and S-5 visibility Cat C/D ¼ SM, and Circling visibility Cat C/D ¼ SM. VDP NA when using CEU altimeter setting. Circling Rwy 17, 35 NA at night.

MALSR

MISSED APPROACH: Climb to 1600 then climbing left turn to 2500 direct ELW VORTAC and hold.

ASOS	GREER APP CON ★	CTAF
120.675	118.8 270.275	123.6 0

One Minute Holding Pattern

ELW VORTAC

CATEGORY	A	B	C	D
S-5	1200-½	441 (500-½)	1200-⅞	441 (500-⅞)
CIRCLING	1260-1 478 (500-1)	1320-1 538 (600-1)	1440-1¾ 658 (700-1¾)	1500-2¼ 718 (800-2¼)

ELEV 782

TDZE 759

Knots	60	90	120	150	180
Min:Seq	5:24	3:36	2:42	2:10	1:48

ANDERSON, SOUTH CAROLINA

Amdt 10C 05SEP24

34°30'N-82°43'W

ANDERSON RGNL (A.ND)

VOR RWY 5

SE-2, 10 JUL 2025 to 07 AUG 2025

SE-2, 10 JUL 2025 to 07 AUG 2025