


RNAV (GPS) RWY 22L
LAFAYETTE RGNL/PAUL FOURNET FLD (LFT)

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). VDP NA with Acadiana Rgnl altimeter setting. When local altimeter setting not received use Acadiana Rgnl altimeter setting and increase all DA 29 feet and all MDA 40 feet; increase LNAV/VNAV visibility all Cats to RVR 3500, increase Circling visibility Cat C/D ¼ SM. For inop MALSR, increase LNAV Cats C and D visibility ¾ mile. For inop MALSR, when using Acadiana Rgnl altimeter setting, increase LNAV/VNAV all Cats visibility to RVR 6000. Baro-VNAV NA when using Acadiana Rgnl altimeter setting.



BOZAN

2000 083° (18.1)

Procedure NA for arrivals at BOZAN on V222 southwest bound.

(IAF) KEBVE

2000 126° (8)

(IF) BEDDY

2000 306° (8)

(IAF) NEYID

2000 313° (16.4)

MYRIC

1041 A

564 A

284 A

MISSED APCH FIX AYOTY

036° 216° 4 NM

230 A

192 A RW22L

(FAF) JILEV

2000 216° (11.9)

1049 A

Procedure NA for arrivals at MYRIC on V20 eastbound.

ELEV	42	D	TDZE	38
------	----	---	------	----

216°

MSA RW22L 25 NM

2900

REIL Rwy 4L, 4R, 11, 22R and 29
MIRL Rwy 11-29 and 4L-22R
HIRL Rwy 4R-22L