

WAAS CH 86900 W32A	APP CRS 326°	Rwy Idg TDZE Apt Elev	5058 82 85
--	------------------------	-----------------------------	---------------------------------------

RNAV (GPS) RWY 32

MILLVILLE MUNI (MIV)

RNP APCH-GPS


▼

▲ NA


Rwy 32 helicopter visibility reduction below $\frac{3}{4}$ SM NA. Baro-VNAV NA when using Atlantic City altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1.5°C or above 54°C . When local altimeter setting not received, use Atlantic City altimeter setting: increase LPV DA to 441 feet; LNAV/VNAV DA to 475 feet and visibility $\frac{1}{8}$ SM; increase all MDAs 60 feet and visibility Cat C and D $\frac{1}{4}$ SM.

MISSED APPROACH: Climb to 2000 direct WIMKA and right turn on track 061° to VCN VOR/DME and hold.

ASOS 119.6	ATLANTIC CITY APP CON 124.6 327.125	UNICOM 123.0 (CTAF) 0
----------------------	---	---------------------------------



ELEV 85	TDZE 82
---------	---------



2000	WIMKA	VCN	VGS and RNAV glidepath not coincident (VGS Angle 3.00/TCH 39).		4 NM
2000	ZUNIE	LAYIB	Holding Pattern		
RW32		2000	146°	2000	GP 3.00° TCH 60
5.7 NM		6.2 NM			
CATEGORY	A	B	C	D	
LPV DA	381-1		299 (300-1)		
LNAV/VNAV DA	415-1		333 (400-1)		
LNAV MDA	480-1 398 (400-1)		480-1 $\frac{1}{8}$	398 (400-1 $\frac{1}{8}$)	
CIRCLING	520-1 435 (500-1)	580-1 495 (500-1)	660-1 $\frac{1}{2}$ 575 (600-1 $\frac{1}{2}$)	660-2 575 (600-2)	

NE-2, 10 JUL 2025 to 07 AUG 2025

NE-2, 10 JUL 2025 to 07 AUG 2025