

WAAS CH <b>86617</b> <b>W14A</b>	APP CRS <b>135°</b>	Rwy Idg TDZE <b>803</b> Apt Elev <b>808</b>
--	------------------------	---

RNAV (GPS) RWY 14

SOUTHERN WISCONSIN RGNL (JVL)

RNP APCH-GPS.

⚠

⚠

Circling Rwy 18 NA at night. Baro-VNAV NA when using Rockford altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 47°C. VDP NA when using Rockford altimeter setting. When local altimeter setting not received, use Rockford altimeter setting and increase LPV DA to 1072 feet, LNAV/VNAV DA to 1291 feet, and all MDAs 80 feet; increase LPV all Cats visibility  $\frac{1}{8}$  SM, LNAV/VNAV all Cats visibility  $\frac{1}{4}$  SM, LNAV Cat C/D visibility  $\frac{1}{4}$  SM, and Circling Cat C/D visibility  $\frac{1}{4}$  SM.

MISSED APPROACH: Climb to 3100 direct TIRRO and hold.

ATIS <b>128.25</b>	ROCKFORD APP CON <b>121.0 327.0</b>	JANESVILLE TOWER ★ <b>118.8(CTAF) 225.4</b>	GND CON <b>121.65</b>	CLNC DEL <b>121.65</b>	UNICOM <b>122.95</b>
-----------------------	--	--	--------------------------	---------------------------	-------------------------

The main chart displays the RNAV (GPS) RWY 14 approach. Key features include:

- Initial Approach:** 3100 NoPT, 135° heading, 4 NM from TAYOR.
- Intermediate Approach:** 2600 NoPT, 135° heading, 2.8 NM from RW14.
- Final Approach:** 1740 NoPT, 135° heading, 1.3 NM from RW14.
- Obstacles:** TAYOR (2049), JESKO (1313), VOGMY (1366), TIRRO (1360), and various other terrain features.
- Procedure Notes:** "Procedure NA for arrivals at TAYOR on V63 northeast bound." and "Procedure NA for arrivals at DAVIS on V216 southwest bound."
- MSA:** Minimum Safe Altitude for RWY 14 is 3100 feet within 2.5 NM.

ELEV 808 D TDZE 803

This inset chart provides details for the local airport area, including:

- Runways:** REIL Rwy 14 and 22, MRL Rwy 18-36, HIRL Rwy 4-22 and 14-32.
- Obstacles:** TWR 892, 863, and other terrain features.
- Navigation:** 7202 X 150, 5004 X 75, and 500 X 150.

4 NM Holding Pattern TAYOR				3100	TIRRO
6000 ← 315°				↑	△
3100 → 135°				*LNAV only.	
GP 3.00° TCH 60				RW14	
6 NM				*1740	
2.6 NM				*1.3 NM to RW14	
1.5 NM				1.3 NM	
CATEGORY	A	B	C	D	
LPV DA	1003-3/4		200 (200-3/4)		
LNAV/VNAV DA	1222-1 1/8		419 (500-1 1/8)		
LNAV MDA	1280-1	477 (500-1)	1280-1 3/8	1280-1 3/8	
			477 (500-1 3/8)	477 (500-1 3/8)	
CIRCLING	1280-1	1320-1	1420-1 3/4	1460-2	
	472 (500-1)	512 (600-1)	612 (700-1 3/4)	652 (700-2)	

JANESVILLE, WISCONSIN

Amdt 1D 16JUN22

42°37'N-89°02'W

SOUTHERN WISCONSIN RGNL (JVL)

RNAV (GPS) RWY 14