

APP CRS	Rwy Idg	7510
312°	TDZE	43
	Apt Elev	46

RNAV (RNP) Z RWY 31

CORPUS CHRISTI INTL (CRP)

▼

For uncompensated Baro-VNAV systems, procedure NA below -1°C (31°F) or above 54°C (130°F). GPS and RF required. For inop MALSR, increase RNP 0.14 all Cats visibility to ¾ mile.

* Missed approach requires minimum climb of 335 feet per NM to 500.

MALSR

MISSED APPROACH: Climb to 2000 on track 312° to ATHIS and hold.

ATIS 126.8	CORPUS APP CON 120.9 348.725	CORPUS TOWER 119.4 257.8	GND CON 121.9 269.15	CLNC DEL 118.55
---------------	---------------------------------	-----------------------------	-------------------------	--------------------

ELEV 46

D

TDZE 43

2000	ATHIS	See planview for multiple IF locations.		SIWOC
fr 312°		GODLU	NIGBE	2400
RW31		646	1200	GP 3.00° TCH 50
1.7 NM		1.7 NM	5.3 NM	
CATEGORY	A	B	C	D
RNP 0.14 DA*		303-1/2	260 (300-1/2)	
RNP 0.30 DA		384-5/8	341 (400-5/8)	
AUTHORIZATION REQUIRED				

CORPUS CHRISTI, TEXAS

Amdt 1A 28NOV24

27°46'N-97°30'W

CORPUS CHRISTI INTL (CRP)

RNAV (RNP) Z RWY 31