

ILS or LOC RWY 9R
OAKLAND COUNTY INTL (PTK)

T Circling Rwy 9L, 36 NA at night. When local altimeter setting not received: see Coleman A Young Muni altimeter setting and increase DA to 1286 feet and all MDA 120 feet, increase S-LOC R9 Cat B visibility to RVR 4000, Cat C/D visibility $\frac{3}{8}$ SM, and Circling Cat B/C/D visibility $\frac{1}{2}$ SM. For inop MALSR, increase S-LOC R9 Cat C/D visibility to $\frac{1}{4}$ SM. For inop MALSR, when using Coleman A Young altimeter, increase SHLS 9R all Cats visibility to RVR 4500, and increase S-LOC R9 Cat C/D visibility to 2 SM. **RVR 1800 authorized with the use of FD or AP or HUD to DA, NA when using Coleman A Young Muni altimeter setting.



MISSED APPROACH:
Climb to 1600 then
climbing right turn
to 3000 direct SVM
VORTAC and hold.

1480 Δ

Δ 1312

1038 Δ 1130 \pm

2700
095°
(6)

275°
1 min
275°

(IF/IAF)
ZUPDU
INT

WAKEL
INT

LOCALIZER 111.1
I-PTK

R-347

R-010

R-360 180°
360°

SALEM
114.3 SVM
Chan 90

MSA PTK 25 NM
2900

ELEV 981 **D** TDZE 981

1750 Δ

OAKLAND COUNTY INTL (PTK)
ILS or LOC RWY 9R