

WAAS CH 99309 W01D	APP CRS 011°	Rwy Idg 9400 TDZE 296 Apt Elev 312
--	------------------------	---

RNAV (GPS) Y RWY 1L

WASHINGTON DULLES INTL (IAD)

RNP APCH - GPS	
----------------	--

- T** For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -13°C or above 54°C. Use of FD or AP required during simultaneous operations. LNAV procedure NA during simultaneous operations. Simultaneous approach authorized.
- A** For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 5500. Increase LNAV Cat C/D visibility to 1 3/4 SM.

ALSF-2



MISSED APPROACH: Climb to 800 then climbing left turn to 3000 direct NHLEN and hold.

D-ATIS	POTOMAC APP CON	DULLES TOWER	GND CON
120.45 306.925 (241°-330°)	120.1 317.8 (Rwy 1R/19L)	121.9 317.8 (EAST)	
128.525 306.925 (091°-240°)	120.25 348.6 (Rwy 1C/19C)	121.625 348.6 (WEST)	
126.1 338.25 (331°-090°)	134.425 348.6 (Rwys 1L/19R and 12/30)		

MISSED APCH FIX



Λ1498


Λ 530

$\Delta 78.5$

CLNC DE

135.7 31

CPDLC



A 1471

(IAF)
HELM7

GRASK

—

$$\frac{1}{2} - \frac{1}{2}$$

SEE IN

SET

--	--

WABER	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 70).	800	3000	NHLEN
-------	---	-----	------	-------


8000 011° 7000 6000 5000 4000 3000 2000

GP 3.00° TCH 55

2.8 NM 2.1 NM 2.4 NM 2.2 NM 2.3 NM 2.4 NM 1.2 NM

1.2 NM to RW01L

CATEGORY		A	B	C	D
LPV	DA	496/18		200 (200-½)	
RNAV/ VNAV	DA	658/35		362 (400-¾)	
RNAV MDA		760/24 464 (500-½)		760/50 464 (500-1)	
CIRCLING		940-1 628 (700-1)		940-1¾ 628 (700-1¾) 1180-2¾ 868 (900-2¾)	



TDZ/CL Rwy 1C, 1L,
1R, 12, 19C, and 19R
REIL Rwy 30
HIRL all Rwys