


WAAS CH 58304 W36A	APP CRS 005°	Rwy Ldg 5264 TDZE 759 Apt Elev 777
---------------------------------	------------------------	---

RNAV (GPS) RWY 36
AUBURN UNIVERSITY RGNL (AUO)

<p>T For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). Baro-VNAV and VDP NA when using Columbus altimeter setting. DME/DME RNP-0.3 NA. When local altimeter setting not received, use Columbus altimeter setting: increase LPV DA to 1072 feet and visibility all Cats ½ SM; increase LNAV/VNAV DA to 1173 feet and visibility all Cats ¾ SM; increase all MDA 120 feet and LNAV Cats C/D visibility ¼ SM and Circling Cats C/D visibility ½ SM. For inop ALS, increase LNAV/VNAV Cat D visibility ¼ SM and LNAV Cat D visibility ½ SM. For inop ALS, when using Columbus altimeter setting, increase LPV all Cats visibility to 1½ SM, LNAV/VNAV all Cats visibility to 1½ SM, and LNAV all Cats visibility to 1¾ SM.</p>	<p>MALSF</p> 	<p>MISSED APPROACH: Climb to 3000 direct RIVME and hold.</p>
--	--	---

AWOS-3PT 132.575	ATLANTA APP CON ★ 125.5 323.1	AUBURN TOWER ★ 123.875	GND CON 121.625	CLNC DEL 118.7 (When tr closed)	UNICOM 123.0 (CTAF) 0
----------------------------	---	----------------------------------	---------------------------	--	--

