

| | | |
|-------------------------|------------------------|---|
| WAAS CH 78300 | APP CRS 269° | Rwy Idg 5000 TDZE 910 Apt Elev 912 |
|-------------------------|------------------------|---|

RNAV (GPS) RWY 27

ANOKA COUNTY/BLAINE (JANES FLD) (A.N.E.)

| | | | | | | |
|---|--|-------------------------------------|--------------------------|--------------------------|--|--|
| RNP APCH - GPS. ▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. When local altimeter setting not received, use Crystal altimeter setting: increase LPV DA to 1131 feet; increase LNAV/VNAV DA to 1361 feet and all visibilities ¼ SM, increase all MDA 40 feet and visibility Cat C/D ¼ SM, and Circling visibility Cat D ¼ SM. Baro-VNAV and VDP NA when using Crystal altimeter setting. For inop ALS when using Crystal altimeter setting, increase LNAV Cat C/D visibility to 1 ¾ SM. | | | | | MALSR | MISSED APPROACH: Climb to 2700 direct GEP VORTAC and hold, continue climb-in-hold to 2700. |
| ATIS 120.625 | MINNEAPOLIS APP CON 126.5 335.65 | ANOKA TOWER★ 132.4 (CTAF) | GND CON 121.85 | CLNC DEL 121.3 | CLNC DEL 121.85 (When twr closed) | UNICOM 122.95 |

