WAAS CH 70526 W05A	APP CRS 054°	Rwy Idg 5502 TDZE 455 Apt Elev 459

RNAV (GPS) RWY 5

MOORE COUNTY (SOP)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. For inop MALSR, increase LNAV/VNAV all Cats visibility to ⅞ mile, LNAV Cats A/B visibility to 1 mile and LNAV Cats C/D visibility to 1⅛ mile. When local altimeter setting not received, use Sanford altimeter setting and increase all DA 88 feet and all MDA 100 feet, increase LNAV/VNAV all Cats visibility ⅛ mile, LNAV Cats C/D visibility ¼ mile, and Circling Cat C ½ mile. When using Sanford altimeter setting, for inop MALSR increase LNAV/VNAV all Cats visibility to 1⅛ mile, LNAV Cats A/B visibility to 1 mile, and LNAV Cat C/D visibility to 1⅜ mile. Baro-VNAV and VDP NA when using Sanford altimeter setting.

MALSR

MISSED APPROACH: Climb to 2500 direct OWWEN and hold.

AWOS-3PT	FAYETTEVILLE APP CON	CLNC DEL	UNICOM
127.575	127.8 343.725	127.0	123.05 (CTAF) L





CATEGORY	A	B	C	D
LPV DA	655-½ 200 (200-½)			
LNAV/VNAV DA	750-½ 295 (300-½)			
LNAV MDA	860-½ 405 (500-½)		860-¾ 405 (500-¾)	
C CIRCLING	880-1 421 (500-1)	920-1 461 (500-1)	1100-1¾ 641 (700-1¾)	1360-3 901 (1000-3)



SE-2, 10 JUL 2025 to 07 AUG 2025
SE-2, 10 JUL 2025 to 07 AUG 2025