

MAYNR THREE DEPARTURE (RNAV)

**TOP ALTITUDE:
ASSIGNED BY ATC**



RNAV 1 - DME/DME/IRU or GPS.
From SLIPT to MAXIM: RNAV 1- GPS.
From SLIPT to CANOA: RNAV 1- GPS.

RADAR required for non-GPS equipped aircraft.
RADAR required.

TAKEOFF MINIMUMS

Rwy 9L: Standard with minimum climb of 500' /NM to 1300.
 Rwy 9R: Standard with minimum climb of 500' /NM to 1500.
 Rwy 13: Standard with minimum climb of 500' /NM to 1800.
 Rwy 27L: Standard with minimum climb of 500' /NM to 1900.
 Rwy 27R: Standard with minimum climb of 500' /NM to 1700.
 Rwy 31: Standard with minimum climb of 500' /NM to 1400.

NOTE: Jet aircraft only.
NOTE: Accelerate to 250K until leaving 10000, if unable, advise ATC.

MSA TMB 25 NM

2900

MIAMI DEP CON	125.5	354.1
ATIS		
124.0		
CLINC DEL		
133.0		
GND CON		
121.7		
MIAMI EXEC TOW		
118.9 (CTAF)		

NOTE: Chart not to scale.

(CONTINUED ON FOLLOWING PAGE)

SE-3, 10 JUL 2025 to 07 AUG 2025

MAYNR THREE DEPARTURE (RNAV)
(MAYNR3.MAYNR) 31OCT24MIAMI, FLORIDA
MIAMI EXEC (TMR)