LOC/DME I-UZA	APP CRS	Rwy Idg	5500
108.5	016°	TDZE	666
Chan 22		Apt Elev	666

ILS Y or LOC Y RWY 2

ROCK HILL/YORK COUNTY/BRYANT FLD (UZA)

T ADF or DME required. VDP NA with Charlotte/Douglas Intl altimeter setting.
NA When local altimeter setting not received, use Charlotte/Douglas Intl altimeter setting and increase all DA 45 feet and all MDA 60 feet. Increase S-LOC 2 Cat C/D visibility ¼ mile. For inop MALSR, increase S-LOC 2 Cat C/D visibility to 1⅛ mile. For inop MALSR, when using Charlotte/Douglas Intl altimeter setting, increase S-LOC 2 Cat C/D visibility to 1⅜ mile.

MALSR

MISSED APPROACH: Climb to 1500 then climbing left turn to 3000 on heading 174° and CLT VOR/DME R-203 to CONEL/I-UZA 12.7 DME/RADAR and hold.

ASOS	CHARLOTTE APP CON	GCO	UNICOM
120.775	120.05 307.8	121.725	123.05 (CTAF) L

GPS REQUIRED FOR TERMINAL ARRIVAL AREA

ALTERNATE MISSED APCH FIX

RALLY
UZ
227
I-UZA 6.6
016°
196°

LOCALIZER 108.5
I-UZA
Chan 22

1020
1037
802
841
115.0 CLT Chan 97
R-203

30 NM to GUCRE
3200
196°
106°
GUCRE

LOM/IAF
RALLY
227 UZ
I-UZA 6.6

(IAF)
GUCRE
3000 NoPT
106°
(8)

(IF/IAF)
CONEL
I-UZA 12.7
RADAR

2500
016°
(6.1)
1289

30 NM to TAGCU
196°
3100
TAGCU
286°

3000 NoPT
286°
(8)
(IAF)
TAGCU

106°
286°
CONEL
3000
30 NM to CONEL (NoPT)

016°
196°
4 NM

ELEV 666 TDZE 666

20
d
5500 X 100
P
A5
2
016°
MIRL Rwy 2-20 L

4 NM
Holding Pattern

CONEL
I-UZA 12.7
RADAR

RALLY LOM
I-UZA 6.6

1500	3000	CLT	CONEL
↑	hdg 174°	R-203	I-UZA 12.7 RADAR

3000
196°
016°
016°
2493
2500
*I-UZA 2.3
I-UZA 1.1
*LOC only.

GS 3.00°
TCH 41

6.1 NM 4.3 NM 1.2 NM

FAF to MAP 5.5 NM

Knots	60	90	120	150	180
Min:Sec	5:30	3:40	2:45	2:12	1:50

CATEGORY	A	B	C	D
S-ILS 2	866-½ 200 (200-½)			
S-LOC 2	1080-½ 414 (500-½)		1080-¾ 414 (500-¾)	
C CIRCLING	1140-1 474 (500-1)	1160-1 494 (500-1)	1340-2 674 (700-2)	1340-2¼ 674 (700-2¼)

SE-2, 10 JUL 2025 to 07 AUG 2025
SE-2, 10 JUL 2025 to 07 AUG 2025