

WAAS CH 93929 W36A	APP CRS 005°	Rwy Idg TDZE 862 Apt Elev 866
--	------------------------	---

RNAV (GPS) RWY 36

METTEL FLD (CEV)

RNP APCH.

NA

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. VDP and Baro VNAV NA when using James M. Cox Dayton Intl altimeter setting. Rwy 36 helicopter visibility reduction below ¾ SM NA. Circling Rwy 4, 22 NA at night. When local altimeter setting not received, use James M Cox Dayton Intl altimeter setting and increase LPV DA to 1253 feet and visibility all Cats to 1½ SM, LNAV/VNAV DA to 1472 feet and visibility all Cats to 1¼ SM, increase all MDA 140 feet and LNAV Cats C/D visibility to 1½ SM, Circling Cat B to 1¼ SM, Cat C to 2¾ SM, and Cat D to 3 SM.

MISSED APPROACH: Climb to 2800 direct RULSE and hold.

AWOS-3 118.325	COLUMBUS APP CON 134.45 352.05	UNICOM 122.8 (CTAF) 0
--------------------------	--	---------------------------------

MISSED APCH FIX

4 NM

185°

005°

RULSE

1081 A

RW36 919

1318 A

1265 A

JULKO 2.5 NM to RW36

1305 A

1328 A

(FAF) YOSKU

2600 005° (6)

2600 005°

(IF/IAF) WALAG

HOLD 6000 2800

4 NM

1491 A

30 NM to WALAG

3000

10 NM to WALAG

2800

WALAG

095°

275°

095°

275°

WALAG

2800

10 NM to WALAG

30 NM to WALAG (NoPT)

3000

4 NM Holding Pattern

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 34).

WALAG

YOSKU

JULKO 2.5 NM to RW36

RW36

2800

RULSE

*LNAV only

6000

2800

185°

005°

005°

2600

*1700

1.6 NM to RW36

GP 3.00° TCH 45

6 NM

2.8 NM

0.9 NM

1.6 NM

CATEGORY	A	B	C	D
LPV DA	1132-7⁄8 270 (300-7⁄8)			
LNAV/VNAV DA	1351-13⁄8 489 (500-13⁄8)			
LNAV MDA	1400-1 538 (600-1)	1400-1½ 538 (600-1½)		
CIRCLING	1440-1 574 (600-1)	1540-1 674 (700-1)	1620-2¼ 754 (800-2¼)	1620-2½ 754 (800-2½)

REIL Rwy 36 0

MIRL Rwy 18-36 0

81

22

6503 X 100

36

005°

CONNERSVILLE, INDIANA

Amtd 3 03JAN19

39°42'N-85°08'W

METTEL FLD (CEV)

RNAV (GPS) RWY 36