RNAV (GPS) RWY 13

FERGUS FALLS MUNI/EINAR MICKELSON FLD (FFM)

WAAS	APP CRS	Rwy Ldg	5639
CH 65920	128°	TDZE	1182
W13A		Apt Elev	1183

RNP APCH - GPS.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter setting not received, use Elbow Lake altimeter setting and increase LPV DA to 1428 feet, increase LNAV/VNAV DA to 1516 feet and all visibilities ⅛ SM; increase all MDAs 60 feet and LNAV Cat C/D and Circling Cat C/D visibility ¼ SM. Baro-VNAV and VDP NA when using Elbow Lake altimeter setting.

MISSED APPROACH: Climb to 2900 direct IGAKE and hold.

AWOS-3PT	MINNEAPOLIS CENTER	UNICOM
119.05	126.1 269.2	122.8 (CTAF) L

Procedure NA for arrivals at WIRDE on V2 northwest bound.

(IAF) WIRDE

2900 NoPT 140° (14)

(IAF) YILUV

2900 NoPT 191° (11.9)

Procedure NA for arrivals at YILUV on V510 northwest bound.

2035±

(IAF) RUSTD

2900 NoPT 086° (22.6)

Procedure NA for arrivals at RUSTD on T407 southbound.

4 NM

128°

308°

(IF/IAF) CUKVU

2900

128° (6.1)

HOLD 6000 2900

(FAF) ITMUW

TUYQU 1.7 NM to RW13

1319±

1637

1339

1629

1288±

RW13

1867

MSA RW13 25 NM

3600

MISSED APCH FIX

128° 4 NM 308°

IGAKE

ELEV 1183

TDZE 1182

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 52).

2900 IGAKE

4 NM Holding Pattern

CUKVU

ITMUW

2900

TUYQU 1.7 NM to RW13

6000 2900 308° 128°

128° 2900

1.1 NM to RW13

RW13

1760

GP 3.00° TCH 40

6.1 NM 3.6 NM 0.6 1.1 NM

CATEGORY	A	B	C	D
LPV DA	1382-¾ 200 (200-¾)			
LNAV/VNAV DA	1470-⅞ 288 (300-⅞)			
LNAV MDA	1580-1 398 (400-1)		1580-1⅛ 398 (400-1⅛)	
CIRCLING	1640-1 457 (500-1)	1740-1 557 (600-1)	1820-1¾ 637 (700-1¾)	1940-2½ 757 (800-2½)

128°

17

3299 X 75

0.7% UP

5639 X 100

35

13

REIL Rwys 13 and 35 L

MIRL Rwys 13-31 and 17-35 L

NC-1, 10 JUL 2025 to 07 AUG 2025

NC-1, 10 JUL 2025 to 07 AUG 2025