

WAAS CH 69316 W17A	APP CRS 180°	Rwy Idg TDZE Apt Elev	6003 213 213
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 17

WEST MEMPHIS MUNI (A WM)

RNP APCH.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 48°C (118°F). When local altimeter setting not received, use Memphis Intl altimeter setting and increase LPV DA to 513 feet, LNAV/VNAV DA to 644 feet and all visibilities ¼ SM; increase all MDAs 60 feet and increase visibility LNAV Cat C and Circling Cat C and D ¼ SM. Baro-VNAV and VDP NA when using Memphis Intl altimeter setting.

MALS R

MISSED APPROACH: Climb to 2100 direct USUPE and hold.

ASOS 118.175	MEMPHIS APP CON 119.1 291.6	CLNC DEL 121.7	UNICOM 123.05 (CTAF) 0
------------------------	---------------------------------------	--------------------------	---

4 NM

360°

180°

(IF/IAF) IMUDE

2500 NoPT (5)

089°

(IAF) JUSON

2500

30 NM to JUSON

089°

360°

2500 NoPT (5)

270°

(IAF) KIDHU

2500

30 NM to KIDHU

270°

360°

2000 (6)

180°

(FAF) HEDIM

340

522

318

369

549

RW17

517

517±

669

669

1001

30 NM to IMUDE (NoPT)

2500

IMUDE

089°

270°

MISSED APCH FIX

USUPE

360°

180°

4 NM

ELEV 213

TDZE 213

180° to RW17

CL

6003 x 100

35

2100

USUPE

*LNAV only.

1

4.4 NM

6 NM

1

4.4 NM

6 NM

1

4.4 NM

6 NM

1

4.4 NM

6 NM

1

4.4 NM

6 NM

1

4.4 NM

6 NM

1

4.4 NM

6 NM

1

4.4 NM

6 NM

2100

USUPE

*LNAV only.

1

4.4 NM

6 NM

1

4.4 NM

6 NM

1

4.4 NM

6 NM

1

4.4 NM

6 NM

1

4.4 NM

6 NM

1

4.4 NM

6 NM

2100

USUPE

*LNAV only.

1

4.4 NM

6 NM

1

4.4 NM

6 NM

1

4.4 NM

6 NM

1

4.4 NM

6 NM

1

4.4 NM

6 NM

1

4.4 NM

6 NM

CATEGORY	A	B	C	D
LPV DA		463-½	250 (300-½)	
LNAV/VNAV DA		594-¾	381 (400-¾)	
LNAV MDA	600-½	387 (400-½)	600-⅝ 387 (400-⅝)	600-1 387 (400-1)
CIRCLING	640-1 427 (500-1)	740-1 527 (600-1)	800-1½ 587 (600-1½)	920-2¼ 707 (800-2¼)

MIRL Rwy 17-35

REIL Rwy 35

WEST MEMPHIS, ARKANSAS

35°08'N-90°14'W

WEST MEMPHIS MUNI (A WM)

RNAV (GPS) RWY 17